

SO SIMPLE
SO STRONG



ELECTRIC FORKLIFT PRONAR



1600-2000



WHEELS

S E R I E S **FB**



MODEL:		jm	FB-16(3)	FB-18(3)	FB-20(3)
Number of wheels			3	3	3
Power type			electric	electric	electric
Rated load capacity	Q	kg	1600	1800	2000
Load centre	c	mm	500	500	500
Wheelbase	y	mm	1420	1420	1538
Total weight (inc. battery)		kg	3100	3180	3345
WHEELS					
Tires type			pneumatic PN / solid SE		
Tires front size		mm	18×7-8	18×7-8	200/50-10
Tires rear size		mm	15×4.5-8	15×4.5-8	15×4.5-8
Tires front/rear (x-drive wheel)			2x/2	2x/2	2x/2
DIMENSIONS					
Mast tilting	α/β	°	6/6	6/6	6/6
Height of mast closed	h1	mm	2085	2085	2085
Full free lifting height	h2	mm	100	100	100
Lifting height	h3	mm	3000	3000	3000
Height of mast open	h4	mm	4070	4070	4070
Overhead guard height	h6	mm	2080	2080	2080
Overall length (without forks)	L2	mm	1955	1955	2075
Overall width	b1	mm	1082	1082	1140
Forks size	l/e/s	mm	920/120/35	1070/100/35	1070/100/35
Ground clearance	m2	mm	90	90	90
AST (pallet 800*1200mm)	Ast	mm	3410	3410	3530
Turning radius	Wa	mm	1615	1615	1725
PERFORMANCE					
Driving speed (load/unload)		km/h	13/14	13/14	13/14
Lifting speed (load/unload)		mm/s	290/440	270/430	250/400
Brake type			Hydraulic	Hydraulic	Hydraulic
ENGINES					
Driving motor		kw	4*2	4*2	4*2
Lifting motor		kw	11	11	11
Battery voltage/capacity		V/Ah	48/500	48/500	48/625
Steering system			AC	AC	AC



Side battery system



Masts: 3000-6500 mm



High class controllers



Multifunctional Display

Some product features described here are optional. Details of specifications and equipment are based on information available at time of printing and may change without notice.

Pronar Sp. z o.o.

Ul. Mickiewicza 101A
17-210 Narew



(+48) 690 299 536



wozki@pronar.pl



Pronar Wózki Widłowe

SO SIMPLE
SO STRONG



ELECTRIC FORKLIFT PRONAR



2500-4000



WHEELS

S E R I E S **FB**



MODEL:		jm	FB-15	FB-20	FB-25
Number of wheels			4	4	4
Power type			electric	electric	electric
Rated load capacity	Q	kg	1500	2000	2500
Load centre	c	mm	500	500	500
Wheelbase	y	mm	1380	1500	1500
Total weight (inc. battery)		kg	3060	4160	4420
WHEELS					
Tires type			pneumatic PN / solid SE		
Tires front size		mm	6.5-10-10PR	7.0-12-12PR	7.0-12-12PR
Tires rear size		mm	5.0-8-8PR	18x7-8-14PR	18x7-8-14PR
Tires front/rear (x-drive wheel)			2x/2	2x/2	2x/2
DIMENSIONS					
Mast tilting	α/β	°	6/12	6/12	6/12
Height of mast closed	h1	mm	2025	2055	2055
Full free lifting height	h2	mm	100	100	100
Lifting height	h3	mm	3000	3000	3000
Height of mast open	h4	mm	4055	4070	4070
Overhead guard height	h6	mm	2125	2125	2125
Overall length (without forks)	L2	mm	2150	2380	2380
Overall width	b1	mm	1090	1150	1150
Forks size	l/e/s	mm	920/120/35	1070/120/40	1070/120/40
Ground clearance	m2	mm	110	120	120
AST (pallet 800*1200mm)	Ast	mm	3805	3960	3960
Turning radius	Wa	mm	1995	2080	2080
PERFORMANCE					
Driving speed (load/unload)		km/h	12/13	12/13	12/13
Lifting speed (load/unload)		mm/s	280/380	300/420	300/420
Brake type			Hydraulic	Hydraulic	Hydraulic
ENGINES					
Driving motor		kw	7,5	11	11
Lifting motor		kw	11	11	11
Battery voltage/capacity		V/Ah	48/620	48/620	48/620
Steering system			AC	AC	AC



Acid or Li-Ion Batteries



Masts: 3000-6500 mm



Multifunctional Display



Levers Control

Some product features described here are optional. Details of specifications and equipment are based on information available at time of printing and may change without notice.

Pronar Sp. z o.o.

Ul. Mickiewicza 101A
17-210 Narew



(+48) 690 299 536



wozki@pronar.pl



Pronar Wózki Widłowe

SO SIMPLE
SO STRONG



ELECTRIC FORKLIFT PRONAR



2500-4000



WHEELS

S E R I E S **FB**



MODEL:		jm	FB-30	FB-35	FB-40	FB-50
Number of wheels			4	4	4	4
Power type			electric	electric	electric	electric
Rated load capacity	Q	kg	3000	3500	4000	5000
Load centre	c	mm	500	500	500	500
Wheelbase	y	mm	1600	1600	2000	2000
Total weight (inc. battery)		kg	5160	5420	7020	7280
WHEELS						
Tires type			pneumatic PN / solid SE			
Tires front size		mm	28x9-15-12PR	28x9-15-12PR	28x12.5-15	28x12.5-15
Tires rear size		mm	18x7-8-14PR	18x7-8-14PR	21x8-9	21x8-9
Tires front/rear (x-drive wheel)			2x/2	2x/2	2x/2	2x/2
DIMENSIONS						
Mast tilting	α/β	°	6/12	6/12	6/9	6/9
Height of mast closed	h1	mm	2070	2070	2250	2250
Full free lifting height	h2	mm	100	100	84	84
Lifting height	h3	mm	3000	3000	3000	3000
Height of mast open	h4	mm	4070	4070	4260	4260
Overhead guard height	h6	mm	2125	2125	2300	2300
Overall length (without forks)	L2	mm	2475	2535	2940	2940
Overall width	b1	mm	1225	1225	1612	1612
Forks size	l/e/s	mm	1070/125/45	1070/125/50	1070/150/50	1070/150/50
Ground clearance	m2	mm	130	130	125	125
AST (pallet 800*1200mm)	Ast	mm	4100	4165	4875	4875
Turning radius	Wa	mm	2215	2280	2705	2705
PERFORMANCE						
Driving speed (load/unload)		km/h	12/13	12/13	12.5/13.5	12.5/13.5
Lifting speed (load/unload)		mm/s	200/340	280/440	290/400	290/400
Brake type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
ENGINES						
Driving motor		kw	12	12	11x2	11x2
Lifting motor		kw	13,5	13,5	25.4	25.4
Battery voltage/capacity		V/Ah	80/500	80/500	80/840	80/840
Steering system			AC	AC	AC	AC



Acid or Li-Ion Batteries



Masts: 3000-6500 mm



Multifunctional Display



Levers Control

Some product features described here are optional. Details of specifications and equipment are based on information available at time of printing and may change without notice.

Pronar Sp. z o.o.

Ul. Mickiewicza 101A
17-210 Narew



(+48) 690 299 536



wozki@pronar.pl



Pronar Wózki Widłowe