

SO SIMPLE
SO STRONG



LPG FORKLIFT PRONAR



1500-2500

S E R I E S **FG**



MODEL:		jm	FG-15*	FG-18*	FG-20*	FG-25*
Number of wheels			4	4	4	4
Power type			LPG/Gasoline	LPG/Gasoline	LPG/Gasoline	LPG/Gasoline
Operation			seat	seat	seat	seat
Rated load capacity	Q	kg	1 500	1 800	2000	2500
Load centre	c	mm	500	500	500	500
Total weight		kg	2 860	2 990	3385	3605
WHEELS						
Tires type			pneumatic PN / solid SE			
Tires front size		mm	6.50-10-10PR	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR
Tires rear size		mm	5.00-8-10PR	5.00-8-10PR	6.00-9-10PR	6.00-9-10PR
DIMENSIONS						
Mast tilting	α/β	°	6/12	6/12	6/12	6/12
Height of mast closed	h1	mm	2 025	2 025	2 055	2 055
Full free lifting height	h2	mm	100	100	100	100
Lifting height	h3	mm	3 000	3 000	3 000	3 000
Height of mast open	h4	mm	4 055	4 055	4 070	4 070
Overhead guard height	h6	mm	2160	2160	2215	2215
Overall length (without forks)	L2	mm	2 285	2 285	2 660	2 660
Overall width	b1	mm	1 082	1 082	1 150	1 150
Forks size	l/e/s	mm	1070/120/35	1070/120/40	1070/120/40	1070/120/40
Ground clearance	m2	mm	120	120	165	165
AST (pallet 800*1200mm)	Ast	mm	3 700	3 700	4 120	4 120
Turning radius	Wa	mm	2 100	2 100	2 365	2 365
PERFORMANCE						
Driving speed (load/unload)		km/h	14.5	14.5	19	19
Lifting speed (load/unload)		mm/s	500/550	500/550	450/470	400/470
Lowering speed (load/unload)		mm/s	530/400	530/400	470/350	470/350
Brake type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
POWER & TRANSMISSION						
Battery		V/Ah	12/60	12/60	12/90	12/90
Engine manufacturer			Nissan	Nissan	Nissan	Nissan
Engine model			K21	K21	K21/K25	K21/K25
Rated Output / r.p.m. PSI		kW			-	-
Rated Output / r.p.m. K25		kW			-	-
Rated Output / r.p.m. K21		kW	31.5 / 2300	31.5 / 2300	31.2 / 2250	31.2 / 2250
Fuel Tank Capacity		L	50	50	50	50
Transmission Type			Powershift	Powershift	Powershift	Powershift

* STANDARD oraz PREMIUM



Dual Power System:
LPG & Gasoline



Equipment Options



Levers Control



Masts 3000-6500 mm

Some product features described here are optional. Details of specifications and equipment are based on information available at time of printing and may change without notice.

Pronar Sp. z o.o.

Ul. Mickiewicza 101A
17-210 Narew



(+48) 690 299 536



wozki@pronar.pl



Pronar Wózki Widłowe

SO SIMPLE
SO STRONG



LPG FORKLIFT PRONAR

 **3000-4500**
LOAD
CAPACITY

S E R I E S **FG**



MODEL:		jm	FG-30*	FG-35*	FG-40	FG-45
Number of wheels			4	4	4	4
Power type			LPG/Gasoline	LPG/Gasoline	LPG/Gasoline	LPG/Gasoline
Operation			seat	seat	seat	seat
Rated load capacity	Q	kg	3000	3500	4000	4500
Load centre	c	mm	500	500	500	500
Total weight		kg	4460	4750	6200	6400
WHEELS						
Tires type			pneumatic PN / solid SE			
Tires front size		mm	28×9-15-12PR	28×9-15-12PR	8.25-15-14PR	300-15-18PR
Tires rear size		mm	6.50-10-10PR	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR
DIMENSIONS						
Mast tilting	α/β	°	6/12	6/12	6/12	6/12
Height of mast closed	h1	mm	2 070	2 070	2245	2245
Full free lifting height	h2	mm	100	100	160	160
Lifting height	h3	mm	3 000	3 000	3000	3000
Height of mast open	h4	mm	4 070	4 070	4170	4170
Overhead guard height	h6	mm	2235	2235	2310(2345)	2310(2345)
Overall length (without forks)	L2	mm	2 700	2 775	3110	3130
Overall width	b1	mm	1 225	1 225	1420	1490
Forks size	l/e/s	mm	1070/125/45	1070/125/50	50×122×1070	50×150×1070
Ground clearance	m2	mm	180	180	230	230
AST (pallet 800*1200mm)	Ast	mm	4 180	4 255	4650	4670
Turning radius	Wa	mm	2 425	2 500	2700	2720
PERFORMANCE						
Driving speed (load/unload)		km/h	19	19	25	25
Lifting speed (load/unload)		mm/s	450/470	400/470	460 / 500	460 / 500
Lowering speed (load/unload)		mm/s	470/350	470/350	460 / 440	460 / 440
Brake type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
POWER & TRANSMISSION						
Battery		V/Ah	12/90	12/90	12/60	12/60
Engine manufacturer			Nissan	Nissan	PSI	PSI
Engine model			K25	K25	PSI 4.3L	PSI 4.3L
Rated Output / r.p.m. PSI		kW	-	-	76 / 2300	76 / 2300
Rated Output / r.p.m. K25		kW	44.2 / 2500	44.2 / 2500	-	-
Rated Output / r.p.m. K21		kW	-	-	-	-
Fuel Tank Capacity		L	50	50	80	80
Transmission Type			Powershift	Powershift	Powershift	Powershift

* STANDARD oraz PREMIUM



Dual Power System:
LPG & Gasoline



Equipment Options



Levers Control



Masts 3000-6500 mm

Some product features described here are optional. Details of specifications and equipment are based on information available at time of printing and may change without notice.

Pronar Sp. z o.o.

Ul. Mickiewicza 101A
17-210 Narew



(+48) 690 299 536



wozki@pronar.pl



Pronar Wózki Widłowe